



Double reading wall light Link

 Collection: Link

 Designer: Émilie Cathelineau

Simple and minimalist, the Link collection frames the light. Depending on the position of the light, the refined line can be fitted vertically or horizontally. Custom dimensions available upon request.

Types of design




Link reading light



Double reading wall light Link



IP Link



IP Link Double

Finishes



Satin Copper



Polished Copper



Satin Brass



Polished Brass



Satin Graphite



Polished Graphite



Satin Nickel



Polished Nickel

Material

Solid Brass

Polycarbonate diffuser

Technical specifications

France et autres

Link double 610

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	500lm	2700°k	7W	Int. power supplier 24V incl.	Yes - Phase cut

Link double 960



Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	1010lm	2700°k	12W	Int. power supplier 24V incl.	Yes - Phase cut

Link double 1300

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	1350lm	2700°k	17W	Int. power supplier 24V incl.	Yes - Phase cut

USA & Canada



Link double 610

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	290lm	2700°k	7W	Int. power supplier 24V incl.	No

Link double 960

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	580lm	2700°k	12W	Int. power supplier 24V incl.	No

Link double 1300

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	770lm	2700°k	17W	Int. power supplier 24V incl.	No



